

## CARVIN SCX1112



SCX1112 12 INCH 2-WAY 600W MONITOR

??????? : ??? ? ? ? ? ? ? ? ?

?????

???????????? ???? :

???????? ???? ? ? ? ? :

???? ? ? ? ? ? ? ? ? :

???? ? ? ? ? ? ? ? ? :

???? :

???? ? ? ? ? ? ? ? ? :

?????? :

????? ? ? ? ? ? ? ? :

[???????? ???? ? ? ? ? ? ? ? ?](#)

?????????

SCX1112 12 INCH 2-WAY 600W MONITOR

- 
- System Type: 12-inch 2-Way, Bass-reflex
  - Frequency Response: 60 Hz – 20 kHz (-10dB); 70 Hz – 18 kHz (-3 dB)
  - Coverage Pattern: Monitor 60x90; Main 90x60
  - Crossover: 2-Way with Speaker Guard™ HF protection
  - Crossover Frequency: 1.8 k Hz (internal)
  - Recommended external crossover frequency: 1.8k Hz @ 12dB/oct. or greater
  - Power Full Range: 300w Continuous / 600w Program /1200w Peak
  - Recommended Amplifier Power: 300 – 900w
  - Sensitivity (1w @ 1m): 96dB
  - Maximum SPL: 120dB Cont. / 126dB Peak
  - LF Driver: 12-inch woofer
  - HF Driver: 1-inch Neodymium 1.75-inch VC
  - Nominal Impedance full range: 8 ohms
  - Bi-amp LF: 8 ohms 300w /600w /1200w
  - Bi-amp HF: 8 ohms 60w /120w /240w
  - Enclosure: 13-Ply Premium Russian Baltic Birch

- Suspension/Mounting: 1-3/8-inch pole mount cup
  - Finish: Black DuraTex™
  - Transport: 1 Recessed Handle SCX1112
  - Grill: Black powder coated 16-Ga steel
  - Connectors: Two 4-pin twist lock connectors
  - Two 1/4-inch connectors
  - Dimensions: 14.5 in high x 15.5 in wide x 22 in deep (370 mm x 395 mm x 559 mm)
  - Net Wt: 33 lb (15 kg)
  - Made in San Diego, California
- 

SCX1112

????????

???????? ???? ???? ???? ???? ???? ???? ????.